

Product type designation

SIPLUS S7-1200 CM 1243-5

"SIPLUS S7-1200cm 1243-5," -25...+55°C with conformal coating based on 6GK7243-5DX30-0XE0 . Communication module CM 1243-5, for connecting S7-1200 to PROFIBUS as DP master module



Figure similar

Transmission rate

Transfer rate

- at the 1st interface / acc. to PROFIBUS 9.6 kbit/s ... 12 Mbit/s

Interfaces

Number of interfaces / acc. to Industrial Ethernet

0

Number of electrical connections

- at the 1st interface / acc. to PROFIBUS 1
- for power supply 1

Type of electrical connection

- at the 1st interface / acc. to PROFIBUS 9-pin Sub-D socket (RS485)
- for power supply 3-pole terminal block

Supply voltage, current consumption, power loss

Type of voltage / of the supply voltage

DC

Supply voltage / external

24 V

Supply voltage / external / at DC / Rated value

24 V

Relative positive tolerance / at DC / at 24 V

20 %

Relative negative tolerance / at DC / at 24 V	20 %
Consumed current <ul style="list-style-type: none"> • from external supply voltage / at DC / at 24 V / typical 	0.1 A
Power loss [W]	2.4 W

Permitted ambient conditions

Ambient temperature <ul style="list-style-type: none"> • during operation • for vertical installation / during operation • for horizontally arranged busbars / during operation • during storage • during transport 	<p>-25 ... +55 °C</p> <p>-25 ... +45 °C</p> <p>-25 ... +55 °C</p> <p>-40 ... +70 °C</p> <p>-40 ... +70 °C</p>
Ambient condition / relating to ambient temperature - air pressure - installation altitude	-25 ... +55°C at 1080 hPa ... 795 hPa (-1000 m ... +2000 m) // -25 ... +45°C at 795 hPa ... 658 hPa (+2000 m ... +3500 m) // -25 ... +35°C at 658 hPa ... 540 hPa (+3500 m ... +5000 m)
Relative humidity / with condensation / maximum	100 %; r.F., incl. condensation/frost permitted (no commissioning in bedewed state)
Resistance to biologically active substances <ul style="list-style-type: none"> • conformity acc. to EN 60721-3-3 	Yes; Compliance with EN 60721-3-3, Class 3B2 mold, fungus, and sponge spores (except fauna). The supplied plug covers must remain in place over the unused interfaces during operation!
Resistance to chemically active substances <ul style="list-style-type: none"> • conformity acc. to EN 60721-3-3 	Yes; Compliant with EN 60721-3-3, Class 3C4 incl. salt spray in accordance with EN 60068-2-52 (severity 3); the supplied plug covers must remain in place on the unused interfaces during operation.
Resistance to mechanically active substances <ul style="list-style-type: none"> • conformity acc. to EN 60721-3-3 	Yes; Compliant with EN 60721-3-3, Class 3S4 incl. sand, dust; the supplied plug covers must remain in place on the unused interfaces during operation.
Protection class IP	IP20

Design, dimensions and weight

Module format	Compact module S7-1200 single width
Width	30 mm
Height	100 mm
Depth	75 mm
Net weight	0.134 kg
Mounting type <ul style="list-style-type: none"> • 35 mm DIN rail mounting • S7-300 rail mounting • wall mounting 	<p>Yes</p> <p>No</p> <p>Yes</p>

Product properties, functions, components / general

Number of units	
<ul style="list-style-type: none"> per CPU / maximum 	1
Performance data / PROFIBUS DP	
Service / as DP master	
<ul style="list-style-type: none"> DPV1 	Yes
Number of DP slaves / on DP master / usable	16
Amount of data	
<ul style="list-style-type: none"> of the address area of the inputs / as DP master / total 	512 byte
<ul style="list-style-type: none"> of the address area of the outputs / as DP master / total 	512 byte
<ul style="list-style-type: none"> of the address area of the inputs / per DP slave 	244 byte
<ul style="list-style-type: none"> of the address area of the outputs / per DP slave 	244 byte
<ul style="list-style-type: none"> of the address area of the diagnostic data / per DP slave 	240 byte
Service / as DP slave	
<ul style="list-style-type: none"> DPV0 	No
<ul style="list-style-type: none"> DPV1 	No

Performance data / S7 communication	
Number of possible connections / for S7 communication	
<ul style="list-style-type: none"> maximum 	8
<ul style="list-style-type: none"> with PG connections / maximum 	1
<ul style="list-style-type: none"> with PG/OP connections / maximum 	3
<ul style="list-style-type: none"> Note 	max. 4 connections to other S7 stations

Performance data / multi-protocol mode	
Number of active connections / with multi-protocol mode	
<ul style="list-style-type: none"> without DP / maximum 	8
<ul style="list-style-type: none"> with DP / maximum 	8

Performance data / telecontrol	
Protocol / is supported	
<ul style="list-style-type: none"> TCP/IP 	No

Product functions / management, configuration	
Configuration software	
<ul style="list-style-type: none"> required 	STEP 7 Basic/Professional V11 (TIA Portal) or higher

Further Information / Internet Links	
Internet-Link	
<ul style="list-style-type: none"> to website: Selector SIMATIC NET SELECTION TOOL 	http://www.siemens.com/snst

- to website: Industrial communication
- to website: Industry Mall
- to website: Information and Download Center
- to website: Image database
- to website: CAx Download Manager
- to website: Industry Online Support

<http://www.siemens.com/simatic-net>
<http://www.siemens.com/industrial-controls/mall>
<http://www.siemens.com/automation/net/catalog>
<http://automation.siemens.com/bilddb>
<http://www.siemens.com/cax>
<http://support.automation.siemens.com>

Security information

Security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a comprehensive industrial security concept. Siemens products and solutions undergo continuous development with this factor in mind. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action (e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Products used from other manufacturers should also be taken into account here. You can find more information on Industrial Security at <http://www.siemens.com/industrialsecurity>. To stay informed about product updates as they occur, sign up for our product-specific newsletter. You can find more information on this at <http://support.automation.siemens.com>. Version 3.4
 14.11.2013- Siemens AG, I IA L CG, Nuremberg

last modified:

02/13/2019