

SIPLUS S7-1500 PM 1507 24V/3A  
 SIPLUS S7-1500 PM 1507 24 V/3 A -40 ... +70 DEGREE C WITH  
 CONFORMAL COATING BASED ON 6EP1332-4BA00 .  
 STABILIZED POWER SUPPLY INPUT: 120/230 V AC OUTPUT: 24  
 V/3 A DC



Figure similar

Input	
Input	1-phase AC
Supply voltage	
• 1 at AC Rated value	120 V
• 2 at AC Rated value	230 V
• Note	Automatic range selection
Input voltage	
• 1 at AC	85 ... 132 V
• 2 at AC	170 ... 264 V
Wide-range input	No
Overvoltage resistance	2.3 × Vin rated, 1.3 ms
Mains buffering at Iout rated, min.	20 ms; at Vin = 93/187 V
Rated line frequency 1	50 Hz
Rated line frequency 2	60 Hz
Rated line range	45 ... 65 Hz
Input current	
• at rated input voltage 120 V	1.4 A

<ul style="list-style-type: none"> <li>at rated input voltage 230 V</li> </ul>	0.8 A
Switch-on current limiting (+25 °C), max.	23 A
Duration of inrush current limiting at 25 °C <ul style="list-style-type: none"> <li>maximum</li> </ul>	3 ms
I <sup>2</sup> t, max.	1.3 A <sup>2</sup> ·s
Built-in incoming fuse	T 3,15 A/250 V (not accessible)
Protection in the mains power input (IEC 898)	Recommended miniature circuit breaker: 10 A characteristic B or 6 A characteristic C

### Output

Output	Controlled, isolated DC voltage
Rated voltage V <sub>out</sub> DC	24 V
Total tolerance, static ±	1 %
Static mains compensation, approx.	0.1 %
Static load balancing, approx.	0.1 %
Residual ripple peak-peak, max.	50 mV
Spikes peak-peak, max. (bandwidth: 20 MHz)	150 mV
Product function Output voltage adjustable	No
Status display	LED green for 24 V OK; LED red for error; LED yellow for stand-by
On/off behavior	No overshoot of V <sub>out</sub> (soft start)
Startup delay, max.	1.5 s
Voltage rise, typ.	10 ms
Rated current value I <sub>out</sub> rated	3 A
Current range	0 ... 3 A
Supplied active power typical	72 W
Short-term overload current <ul style="list-style-type: none"> <li>on short-circuiting during the start-up typical</li> <li>at short-circuit during operation typical</li> </ul>	12 A 12 A
Duration of overloading capability for excess current <ul style="list-style-type: none"> <li>on short-circuiting during the start-up</li> <li>at short-circuit during operation</li> </ul>	70 ms 70 ms
Parallel switching for enhanced performance	No

### Efficiency

Efficiency at V <sub>out</sub> rated, I <sub>out</sub> rated, approx.	87 %
Power loss at V <sub>out</sub> rated, I <sub>out</sub> rated, approx.	11 W

### Closed-loop control

Dynamic mains compensation (V <sub>in</sub> rated ±15 %), max.	0.1 %
Dynamic load smoothing (I <sub>out</sub> : 50/100/50 %), U <sub>out</sub> ± typ.	1 %
Dynamic load smoothing (I <sub>out</sub> : 10/90/10 %), U <sub>out</sub> ± typ.	3 %
Load step setting time 10 to 90%, typ.	5 ms

Load step setting time 90 to 10%, typ.	5 ms
Setting time maximum	5 ms

### Protection and monitoring

Output overvoltage protection	Additional control loop, limitation (closed loop control) at < 28.8 V
Current limitation	3.15 ... 3.6 A
Current limitation, typ.	3.4 A
Property of the output Short-circuit proof	Yes
Short-circuit protection	Electronic shutdown, automatic restart
Overload/short-circuit indicator	-

### Safety

Primary/secondary isolation	Yes
Galvanic isolation	Safety extra-low output voltage $U_{out}$ acc. to EN 60950-1 and EN 50178 and EN 61131-2
Protection class	Class I
Leakage current	
• maximum	3.5 mA
• typical	0.4 mA
CE mark	Yes
UL/cUL (CSA) approval	cULus-Listed (UL 508, CSA C22.2 No. 142), File E143289
Explosion protection	IECEX Ex nA nC IIC T4 Gc; ATEX (EX) II 3G Ex nA nC IIC T4 Gc; cULus (ANSI/ISA 12.12.01, CSA C22.2 No.213) Class I, Div. 2, Group ABCD, T4, File E330455
FM approval	Class I, Div. 2, Group ABCD, T4
CB approval	Yes
Marine approval	ABS, BV, DNV GL
Degree of protection (EN 60529)	IP20

### EMC

Emitted interference	EN 55022 Class B
Supply harmonics limitation	EN 61000-3-2
Noise immunity	EN 61000-6-2

### Operating data

Ambient temperature	
• during operation	-40 ... +70 °C
— Note	with natural convection
• during transport	-40 ... +85 °C
• during storage	-40 ... +85 °C
Humidity class according to EN 60721	Climate class 3K3, no condensation
Ambient condition relating to ambient temperature - air pressure - installation altitude	$T_{min}$ ... $T_{max}$ at 1140 hPa ... 795 hPa (-1000 m ... +2000 m); $T_{min}$ ... ( $T_{max} - 10K$ ) at 795 hPa ... 658 hPa (+2000 m ... +3500 m); $T_{min}$ ... ( $T_{max} - 20K$ ) at 658 hPa ... 540 hPa (+3500 m ... +5000 m)

Relative humidity with condensation maximum	100 %; Relative humidity, incl. condensation/frost permitted (no commissioning under condensation conditions)
Resistance to biologically active substances conformity acc. to EN 60721-3-3	Yes; Compliant with EN 60721-3-3, Class 3B2 mold and fungal spores (except fauna); the supplied plug covers must remain in place on the unused interfaces during operation.
Resistance to chemically active substances conformity acc. to EN 60721-3-3	Yes; Compliant with EN 60721-3-3, Class 3C4 incl. salt spray in accordance with EN 60068-2-52 (severity 3); the supplied plug covers must remain in place on the unused interfaces during operation.
Resistance to mechanically active substances conformity acc. to EN 60721-3-3	Yes; Conformity with EN 60721-3-3, Class 3S4 incl. Sand, dust. The supplied connector covers must remain on the unused interfaces during operation!

## Mechanics

Connection technology	Screw-/spring clamp connection
Connections	
<ul style="list-style-type: none"> <li>• Supply input</li> <li>• Output</li> </ul>	<p>L, N, PE: 1 screw terminal each for 0.5 ... 2.5 mm<sup>2</sup></p> <p>L+, M: 2 spring-loaded terminals each for 0.5 to 2.5 mm<sup>2</sup></p>
Product function	
<ul style="list-style-type: none"> <li>• removable terminal at input</li> <li>• removable terminal at output</li> </ul>	<p>Yes</p> <p>Yes</p>
Width of the enclosure	50 mm
Height of the enclosure	147 mm
Depth of the enclosure	129 mm
Required spacing	
<ul style="list-style-type: none"> <li>• top</li> <li>• bottom</li> <li>• left</li> <li>• right</li> </ul>	<p>50 mm</p> <p>50 mm</p> <p>0 mm</p> <p>0 mm</p>
Weight, approx.	0.45 kg
Product feature of the enclosure housing for side-by-side mounting	Yes
Installation	Can be mounted onto S7-1500 rail
MTBF at 40 °C	1 611 993 h
Other information	Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)