

SITOP PSU100P 24 V/8 A IP67
 SITOP PSU100P IP67 Stabilized power supply input: 120/230 V AC,
 output: 24 V DC/8 A



Input	
Input	1-phase AC
Supply voltage	
<ul style="list-style-type: none"> • 1 at AC Rated value • 2 at AC Rated value • Note 	120 V 230 V Automatic range selection
Input voltage	
<ul style="list-style-type: none"> • 1 at AC • 2 at AC 	85 ... 132 V 170 ... 264 V
Wide-range input	No
Overvoltage resistance	Implemented internally with varistor
Mains buffering at I _{out} rated, min.	40 ms; at V _{in} = 120/230 V
Rated line frequency 1	50 Hz
Rated line frequency 2	60 Hz
Rated line range	47 ... 63 Hz
Input current	
<ul style="list-style-type: none"> • at rated input voltage 120 V • at rated input voltage 230 V 	3.5 A 1.52 A
Switch-on current limiting (+25 °C), max.	15 A

I ² t, max.	0.6 A ² ·s
Built-in incoming fuse	T 6.3 A
Protection in the mains power input (IEC 898)	Recommended miniature circuit breaker: from 6 A characteristic C/B

Output

Output	Controlled, isolated DC voltage
Rated voltage V _{out} DC	24 V
Total tolerance, static ±	3 %
Static mains compensation, approx.	0.1 %
Static load balancing, approx.	0.2 %
Residual ripple peak-peak, max.	50 mV
Spikes peak-peak, max. (bandwidth: 20 MHz)	100 mV
Product function Output voltage adjustable	No
Status display	Green LED: 24 V OK; red LED flashing: "overload/short-circuit"
Signaling	Relay contact (NO contact, rating 30 V AC/ 0.5 A; 30 V DC/1 A) for 24 V OK
On/off behavior	Overshoot of V _{out} < 3 %
Startup delay, max.	1.5 s
Voltage rise, typ.	23 ms
Voltage increase time of the output voltage maximum	100 ms
Rated current value I _{out} rated	8 A
Current range	0 ... 8 A
Supplied active power typical	206 W
Short-term overload current	
• on short-circuiting during the start-up typical	30 A
• at short-circuit during operation typical	30 A
Duration of overloading capability for excess current	
• on short-circuiting during the start-up	50 ms
• at short-circuit during operation	50 ms
Parallel switching for enhanced performance	Yes; Symmetric wiring required
Numbers of parallel switchable units for enhanced performance	2

Efficiency

Efficiency at V _{out} rated, I _{out} rated, approx.	93.6 %
Power loss at V _{out} rated, I _{out} rated, approx.	13.1 W

Closed-loop control

Dynamic mains compensation (V _{in} rated ±15 %), max.	0.2 %
Dynamic load smoothing (I _{out} : 50/100/50 %), U _{out} ± typ.	1 %
Setting time maximum	2 ms

Protection and monitoring

Output overvoltage protection	< 29 V
Current limitation, typ.	9 A
Property of the output Short-circuit proof	Yes
Short-circuit protection	Electronic shutdown, automatic restart
Enduring short circuit current RMS value	
• maximum	9 A
• typical	8 A
Overload/short-circuit indicator	Red LED flashing for "overload/short-circuit"

Safety

Primary/secondary isolation	Yes
Galvanic isolation	Safety extra-low output voltage U _{out} acc. to EN 60950-1 and EN 50178
Protection class	Class I
Leakage current	
• maximum	3.5 mA
• typical	1 mA
CE mark	Yes
UL/cUL (CSA) approval	cULus-Listed (UL 508, CSA C22.2 No. 107.1)
Explosion protection	No
FM approval	-
CB approval	No
Marine approval	No
Degree of protection (EN 60529)	IP67, enclosure type 5 indoor

EMC

Emitted interference	EN 55022 Class B
Supply harmonics limitation	EN 61000-3-2
Noise immunity	EN 61000-6-2

Operating data

Ambient temperature	
• during operation	-25 ... +60 °C
— Note	with natural convection
• during transport	-40 ... +85 °C
• during storage	-40 ... +85 °C
Humidity class according to EN 60721	3K6 without direct sunlight

Mechanics

Connection technology	screw-type terminals
Connections	
• Supply input	L1, N, PE: Plug connector 7/8" (counterpart see "Operating Instructions (compact)")
• Output	+, -: Plug connector 7/8" (counterpart see "Operating Instructions (compact)")
• Auxiliary	Alarm signals: M12 plug-in connector 4-pin

Product function	
• removable terminal at input	Yes
• removable terminal at output	Yes
Width of the enclosure	120 mm
Height of the enclosure	181 mm
Depth of the enclosure	60.5 mm
Required spacing	
• top	50 mm
• bottom	0 mm
• left	0 mm
• right	0 mm
Weight, approx.	1.3 kg
Product feature of the enclosure housing for side-by-side mounting	Yes
Installation	Wall mounting
MTBF at 40 °C	800 000 h
Other information	Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)