

### Product type designation

### ASM 475 communication module

MOBY communication module ASM475 for SIMATIC S7 300 and ET200M parameterizable (without front connector)



### Suitability for operation

SIMATIC S7-300, ET200M together with RF200/300/600, MV400, MOBY D/E//U

### Transmission rate

Transfer rate / at the point-to-point connection / serial / maximum 115.2 kbit/s

### Interfaces

Design of the interface / for point-to-point connection RS422

Number of readers / connectable 2

#### Type of electrical connection

- of the backplane bus S7-300 backplane bus
- of the PROFIBUS interface (according to the head module)
- of Industrial Ethernet interface (according to the head module)
- for supply voltage Screw-type or spring-loaded terminals

Design of the interface / to the reader / for communication Screw-type or spring-loaded terminals

### Mechanical data

Material Noryl

Color anthracite

## Supply voltage, current consumption, power loss

Supply voltage	
• at DC / Rated value	24 V
• at DC	20 ... 30 V
Consumed current / at DC / at 24 V	
• without connected devices / typical	0.1 A
• with connected devices / maximum	1 A

## Permitted ambient conditions

Ambient temperature	
• during operation	0 ... 60 °C
• during storage	-40 ... +70 °C
• during transport	-40 ... +70 °C
Protection class IP	IP20
Shock resistance	According to IEC 61131-2
Shock acceleration	150 m/s <sup>2</sup>
Vibrational acceleration	10 m/s <sup>2</sup>

## Design, dimensions and weight

Width	40 mm
Height	125 mm
Depth	120 mm
Net weight	0.2 kg
Mounting type	S7-300 rack
Wire length / for RS 422 interface / maximum	1000 m

## Product properties, functions, components / general

Display version	4 LEDs per reader connection, 2 LEDs for device status
Product function / transponder file handler can be addressed	Yes
Protocol / is supported	
• S7 communication	Yes
Type of parameterization	Object manager, GSD
Type of programming	FB 45, FB 55, FC 56 (FC 45/55 with limited functionality)
Type of computer-mediated communication	acyclic communication

## Standards, specifications, approvals

Certificate of suitability	CE, FCC, UL/CSA
----------------------------	-----------------

## Accessories

accessories	Front connector with screw-type or spring-loaded terminals
-------------	--

## Further Information / Internet Links

Internet-Link	
• to website: Selector SIMATIC NET SELECTION TOOL	<a href="https://support.industry.siemens.com/cs/ww/en/view/67384964">https://support.industry.siemens.com/cs/ww/en/view/67384964</a>

- to website: Industrial communication
- to website: Industry Mall
- to website: Information and Download Center
- to website: Image database
- to website: CAx Download Manager
- to website: Industry Online Support

- <http://www.siemens.com/ident/rfid>
- <https://mall.industry.siemens.com>
- <http://www.siemens.com/industry/infocenter>
- <http://automation.siemens.com/bilddb>
- <http://www.siemens.com/cax>
- <https://support.industry.siemens.com>

## Security information

### Security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action (e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <http://www.siemens.com/industrialsecurity>. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <http://support.automation.siemens.com>. (V3.4)

**last modified:**

12/14/2018