



Figure similar

MLFB-Ordering data

6SL3210-5FB10-1UF0

Client order no. :

Item no. :

Order no. :

Consignment no. :

Offer no. :

Project :

Remarks :

| Rated data | | Ambient conditions | |
|-------------------------|---------------------------|----------------------------------|----------------------------------|
| Input | | Cooling | natural convection |
| Number of phases | 1 AC | Installation altitude | 1000 m |
| Line voltage | 200 ... 240 V +10 % -15 % | Ambient temperature | |
| Line frequency | 45 ... 66 Hz | Operation | 0 ... 45 °C |
| Output | | Storage | -40 ... 70 °C |
| Rated power | 0.10 kW | Relative humidity | |
| Rated current (IN) | 1.20 A | Max. operation | 90 % |
| Max. output current | 3.60 A | Standards | |
| Inputs / outputs | | Compliance with standards | CE, KC, cULus, EAC, C-Tick (RCM) |

Standard digital inputs

| | |
|--------|---|
| Number | 4 |
|--------|---|

Digital outputs

| | |
|--------|---|
| Number | 2 |
|--------|---|

Mechanical data

| | |
|----------------------|---------------------|
| Degree of protection | IP20 / UL open type |
| Size | FSB |
| Net weight | 1.25 kg |
| Width | 55.0 mm |
| Height | 170.0 mm |
| Depth | 170.0 mm |